MARKED UP VERSION OF CLAIMS WITH MARKING

TO SHOW CHANGES MADE

- Claim 1. (Currently Annended) A polishing device comprising a body made of porous polyvinyl acetal material having a uniform pore size throughout the core material of the body with over 80% of the pores being below 40 microns in diameter, axid body being coated with a low-viscosity-slurry comprising a hydrophillic urethane based adhesive and mixed abrasive particles of polishing materials which are curred [[te]] on said body to form a thin abrasive skin which is absorbed into the body nores and follows the contour of the popers [forfem] and an outer surface of said body.
- Claim 2. (Original) A polishing device as claimed in claim 1 wherein said abrasive particles are selected from the group consisting of Al₂O₃ and SiO₂ ranging in size from 0.1 microns to about 100.0 microns.
- Claim 3. (Original) A polishing device as claimed in claim 1 wherein said abrasive particles are selected from the group consisting of Al₂O₃ and SiO₂ ranging in size 0.5 micrors to about 7.0 micrors.
- Claim 4. (Original) A polishing device as claimed in claim 1 wherein said abrasive particles are selected from the group consisting of aluminum oxide, beat treated aluminum oxide, white fused aluminum oxide, black silicon carbide, green silicon carbide, silicon nitride, titanium diboride, boron carbide, tungsten carbide, titanium carbide, tentalum carbide, diamond, silica, silicon dioxide, iron oxide, cromia, ceria, cerium oxide, manganese dioxide, zirconia, titania, silicates, tit oxide, cubic boron nitride, garnet, alumina zirconia, zirconiam oxide, sod gel abrasive particles, and combinations thereof.
- Claim 5. (Original) A polishing device as claimed in claim 1 wherein said polyvinyl acetal material has an average pore size of about 20 microns.
 - Claim 6. (Original) A polishing device as claimed in claim 1 wherein the weight of the

adhesive particles is preferably less than 5% of the wight of said slurry.

Claim 7. (Original) A polishing device as claimed in claim 1 wherein said polishing device is a nad.

Claim 8. (Original) A polishing device as claimed in claim 1 wherein said polishing device is a roller.

Claim 9. (Original) A polishing device as claimed in claim 1 wherein said polishing device is a disk.

Claim 10. (Original) A polishing device as claimed in claim 1 wherein said cured skin is less than 1 millimeter in thickness.

Claim 11. (Currently Amended) A polishing device as claimed in claim 1 wherein the weight of the adhesive abrasive particles range from 5% to 80% of the weight of said slurry.

Claim 12. (Currently Amended) A semiconductor polishing device comprising a core body made of porous polyvinyl nettal material having a cylindrical roller shape and a outer surface, said material having a uniform pore size throughout with at least 80% of the pores ranging from about 7 microus to about 40 microns in diameter, a slurry of adhesive hydrophilic polymer offlow-viscosity and abrasive particles ranging from 0.5 to about 100.0 microns and comprising from 5% to 80% of the shurry by weight, axial shurry being coated and cured on said outer surface of said cylindrical roller forming an abrasive skin.

Claim 13. (Original) A semiconductor polishing device as claimed in claim 12 wherein said abrasive particles are selected from the group consisting of aluminum oxide, heat treated aluminum oxide, white fused aluminum oxide, black silicon carbide, green silicon carbide, silicon nairide, titanium diboride, boron carbide, tungsten carbide, titanium carbide, tantalum carbide, diamond, silica, silicon dioxide, iron oxide, chromia, ceria, cerium oxide, manganese dioxide, ziroonia, titania, silicates, tin oxide, cubic boron nitride, garnet, alumina zirconia, zirconium oxide, sol gel abrasive particles, and combinations thereof.

Claim 14. (Currently Amended) A semiconductor polishing device as claimed in claim 12 wherein said adhesive is selected from the group consisting of allphatic polyether urtheane ursthans; methacrylate, aromatic diffunctional polyether urethane methacrylate and allphatic urethane acrylate.

Claim 15. (Currently Amended) A semiconductor polishing device as claimed in claim 12 wherein said abrasive skin [[has]] comprises composite particles having a size of about 1.2 microns.

Claim 16. (Original) A semiconductor polishing device as claimed in claim 12 wherein said abrasive skin is about 1.0 microns in thickness.

Claim 17. (Currently Amended) A semiconductor polishing device comprising a substantially cylindrical roller body made of polyvinyl acetal with its core having uniform material porosity with 80% of its pores ranging from 7 to 40 microns and an abrasive particle and low viacosity urethane adhesive composite skin cured to said [[core]] <u>lody</u>, said <u>urethane</u> adhesive being selected from the group consisting of allphatic polyether urtheane methacrylate, aromatic difunctional polyether urethane methacrylate and allphatic urethane acrylate, said skin ranging in thickness from 0.5 to 7.0 microns.

Claim 18. (Currently Amended) A semiconductor pollubing device comprising a [[core]] body made of porous polyvinyl acetal material baving a cylindrical roller shape and a outer surface, said material having a uniform pore size throughout with at least 80% of the pores ranging from about 7 microns to about 40 microns in diameter with a fluid flow through rate which does not distort the roller during the polithing process, a slurry comprising an adhesive of polyvinyl acetal material mixed with water and a compositie abrasive material, said slurry having a viscosity less than the viscosity of suite core the polyvinyl acetal material mixed with a compositie abrasive material mounted in carrier particles of composite abrasive material mounted in carrier particles of polyvinyl acetal, said slurry being coated and cured on said outer surface of said cylindrical roller to form

an abrasive skin.

- Claim 19. (Currently Amended) A semiconductor eleming <u>polishing</u> device as claimed in claim 18 wherein said metal is are abrasive material particle is selected from the group consisting of aluminum oxide, beat treated aluminum oxide, white fused aluminum oxide, black silicon carbide, green silicon carbide, silicon nieride, titanium diborde, boron carbide, tungsten carbide, titanium carbide, tantahum carbide, diamond, silica, silicon dioxide, iron oxide, chromia, ceria, cerium oxide, manganese dioxide, zirconia, titania, silicates, tin oxide, cubic boron nitride, garnet, alumina zirconia, zirconium oxide, sol cel abrasive particles, and combinations thereof.
- Claim 20. (Currently Amended) A process of making a semiconductor polishing roller comprising of the steps of:
 - a. moking a roller <u>body</u> of clean [[PVA]] <u>porous polyvinyl acetal sponge</u> with over 80% of the pores of <u>said porous polyvinyl acetal sponge</u> ranging from about 7 micrors to about 40 microns in diameter;
 - applying a coating of a sturry comprising an adhesive having a tow viscosity and abrasive particles to the outer surface of said roller to form a skin; and
 - c. curing said slurry skin to said roller body with ultra violet light forming a unitary roller device with a thin abrasive skin.
- Claim 21. (Original) A process of making a semiconductor polishing roller as claimed in claim 20 wherein said curing takes place over a period ranging from .1 minutes to 5 minutes.
- Claim 22. (Original) A process of making a semiconductor polishing roller as claimed in claim 20 wherein said curing takes place in about 1 minute at about 300 watts.
- Claim 23. (Original) A process of making a semiconductor polishing roller as claimed in claim 20 wherein said coating applied is less than 0.2mm in thickness.

- Claim 24. (Currently Amended) A claim according to process of making a semiconductor
 polishing roller as claimed in claim 20 wherein and abrasive materiath particles are selected from the
 group consisting of aluminum coxide, best treated aluminum oxide, white fissed aluminum oxide, black
 silicon carbide, green silicon carbide, silicon niride, titanium diboride, boren carbide, tutanium carbide, carbide,
- Claim 25. (Currently Amended) A chaim according to process of making a semiconductor polishing roller as claimed in claim 20 wherein said low viscosity adhesive is selected from the group consisting of formulated allphatic polyether urethane methacrylate, aromatic difunctional polyether urethane methacrylate; formulated multifunctional allphatic urethane acrylate and combinations thereof.
 - Claim 26. (Canceled)
- Claim 27. (New) A polishing device as claimed in claim 1 wherein said polyvinyl acetal body has a durometer ranging from 5-9 depending upon wetness of the material.
- Claim 28. (New) A polishing device as claimed in claim 1 wherein said porous polyvinyl acetal body has a pore size ranging from about 7 microns to about 40 microns for at least 90% of the pores.
- Claim 29. (New) A polishing device as claimed in claim 1 wherein the weight of abrasive particles to the weight of urethane based adhesive ranges from about 30% to about 50%.
- Claim 30. (New) A polishing device as claimed in claim 1 wherein said urethane based adhesive is selected from the group consisting of formulated alliphatic polyether urethane methacrylate, aromatic difunctional polyether urethane methacrylate; formulated multifunctional alliphatic urethane

acrylate and combinations thereof.